


# Convertible Console

## YOCA 36 to 60 / YOHA 24 to 60



### Technical features

Set reference		YOHC				
Models	Sizes	24	36	48	60	
Cooling capacity	kW	7.03	10.55	14.07	17.58	
Heating capacity	kW	8.15	11.43	15.24	18.11	
Compressor	Type	Rotary		Scroll		
Refrigerant		R22				
Power supply	V/Ph/Hz	230 / 1 / 50 + E		400 / 3 / 50 + E + N		
Power input	cooling	kW	2.80	3.70	4.70	6.57
	heating	kW	2.89	3.35	4.90	6.90
EER	w	2.51	2.85	2.99	2.68	
COP	w	2.82	3.41	3.11	2.62	
Operating current	A	12.10	21.00	8.20	10.00	
Indoor airflow (high / low speed)	m³/h	1 200 / 700	1 600 / 1 000	2 000 / 1 600	2 200 / 1 600	
Sound pressure at 1 m	Indoor (H/M/L)	dB(A)	45 / 43 / 40	45 / 43 / 40	47 / 46 / 44	47 / 46 / 44
	Outdoor	dB(A)	52	57	55	62
Dimensions	Indoor	H (mm)	660	660	680	680
		W (mm)	995	1 285	1 670	1 670
		D (mm)	199	198	240	240
	Outdoor	H (mm)	860	960	960	1 245
		W (mm)	895	990	990	940
		D (mm)	330	360	360	360
Net weight	Indoor unit	kg	27	35	52	52
	Outdoor unit	kg	62	90	88	110
Piping	Type of connection		Flare			
	Diameter	Gas	5/8"	3/4"	3/4"	3/4"
		Liquid	3/8"	1/2"	1/2"	1/2"
Refrigerant charge	g	2 300	2 800	3 100	3 900	
Pipe run	Length	m	20	25	25	30
	Height	m	10	10	10	15
Operating limits - cooling mode	min/max	+18°C / +45°C				
Operating limits - heating mode	min/max	-7°C / +24°C				

Nominal cooling capacity based on : - Indoor Air Temp. 27°C DB / 19°C WB - Outdoor Air Temp. 35°C DB

Nominal heating capacity based on : - Indoor Air Temp. 21°C DB - Outdoor Air Temp. 7°C DB/6°C WB

Piping length : 7.5 m with initial charge

### Options / Accessories

Sizes		24	36	48	60
Wired control	O			AMR01Y	
Weekly timer control	O			AMR02M	
Centralised control	O			AMR03M	
Condensate pump	A	AMP01C			AMP02B
Wall mounting kit	A				
Floor mounting kit	A			AMF44B	

O= option (factory fitted) A= accessory (supplied loose)



E-COM-M0951 Manufacturer reserves the rights to change specifications without prior notice.

